# NSN 5950-00-204-7982

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-204-7982

## Reliability Indicator:

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.090 inches single mounting facility single center group and 2.010 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

1.090 inches single mounting facility single center group and 2.010 inches single mounting facility single center group

### Mounting Hole Diameter:

0.193 inches single group and 0.199 inches single group

## **Frequency Rating:**

50.0 hertz single component and 440.0 hertz single component

## Input-output Phase Relationship:

Single phase to single phase single component

#### Winding Shielding Method:

Internal shield grounded to inclosure single component

## **Body Length:**

## 2.820 inches

**Body Width:** 

2.750 inches

#### Body Height:

2.250 inches

## Maximum Operating Temp:

120.0 degrees celsius

## Inclosure Type:

Fully enclosed

#### **Mounting Facility Quantity:**

4 single group

#### **Mounting Method:**

Flange single group and unthreaded hole single group

## Winding Function And Quantity:

1 primary single component and 1 secondary single component

#### Winding Operating Current:

1.0 amperes ac single component single secondary

#### Winding Operating Voltage:

85.00 ac volts single component single secondary

#### Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

## Demilitarization:

No

# NSN 5950-00-204-7982

Power Transformer - Page 2 of 2

**Fiig:** A058b0

