

View Online at <https://aerobasegroup.com/nsn/5950-00-208-4197>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.151 inches single group and 0.161 inches single group

Impedance Rating In Ohms:

600.0 single component single primary

Frequency Rating:

300.0 hertz single component and 4.0 kilohertz single component

Maximum Transformer Power Rating:

500.0 milliwatts single component

Primary To Secondary Turn Ratio:

10 to 1 single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

Between 0.875 inches and 0.937 inches

Body Width:

Between 0.719 inches and 0.781 inches

Body Height:

Between 0.719 inches and 0.781 inches

Maximum Operating Temp:

131.0 degrees celsius

Distance Between Mounting Facility Centers:

0.593 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Features Provided:

Color coded lead

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0