

View Online at <https://aerobasegroup.com/nsn/5950-00-211-7138>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.177 inches single mounting facility single center group and 1.197 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.177 inches single mounting facility single center group and 1.197 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

Between 1.570 inches and 1.610 inches

Body Width:

Between 1.570 inches and 1.610 inches

Body Height:

Between 2.290 inches and 2.330 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

56.0 milliamperes ac single component single secondary

Winding Operating Voltage:

71.00 ac volts single component single secondary

Test Data Document:

10001-2806972 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

4 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0