## NSN 5950-00-217-8241

Reactor-transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-217-8241

**Reliability Indicator:** Not established **Overall Length:** 3.062 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.297 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 1.859 inches single mounting facility single center group **Overall Height:** 4.750 inches **Overall Width:** 2.625 inches **Inductance Rating:** 1.00 microhenries 2nd component single winding Frequency Rating: 57.0 hertz 1st component and 63.0 hertz 1st component Input-output Phase Relationship: Single phase to single phase 1st component **Winding Shielding Method:** Grounded to inclosure, core and mounting 1st component **Maximum Operating Temp:** 50.0 degrees celsius **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 4 single group **Mounting Method:** Threaded stud single group **Rating Method:** Electrical 2nd component single winding **Winding Function And Quantity:** 1 primary 1st component and 1 secondary 1st component **Thread Size:** 0.164 inches single group **Winding Operating Current:** 70.0 milliamperes dc 1st component single secondary and 200.0 milliamperes dc 1st component single secondary Dc Resistance Rating In Ohms: 25.000 2nd component single winding **Winding Operating Voltage:** 82.00 ac volts 1st component single secondary and 84.00 ac volts 1st component single secondary

Unc single group

**Thread Series Designator:** 

## NSN 5950-00-217-8241

Reactor-transformer - Page 2 of 2



Terminal '	Type And	Quantity:
ı errillinar	I VDE AIIU	Qualitity.

7 solder stud

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A058b0