

View Online at <https://aerobasegroup.com/nsn/5950-00-219-6438>

Reliability Indicator:

Not established

Overall Length:

1.062 inches

Turn Quantity:

18 single component 2nd secondary

Inductance Rating:

3920.00 microhenries single component single primary and 4080.00 microhenries single component single primary

Frequency Rating:

65.0 kilohertz single component and 99.0 kilohertz single component

Coil Form Type:

Solid single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Overall Diameter:

2.000 inches

Maximum Operating Temp:

175.0 degrees celsius

Distance Between Mounting Facility Centers:

1.312 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded stud single group

Rating Method:

Winding turns single component all secondary

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.164 inches single group

Winding Conductor Size:

0.02257 inches american wire gage single component 2nd secondary

Test Data Document:

80063-sc-c-64149 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0