

View Online at <https://aerobasegroup.com/nsn/5950-00-219-6438>

**Reliability Indicator:**

Not established

**Overall Length:**

1.062 inches

**Turn Quantity:**

18 single component 2nd secondary

**Inductance Rating:**

3920.00 microhenries single component single primary and 4080.00 microhenries single component single primary

**Frequency Rating:**

65.0 kilohertz single component and 99.0 kilohertz single component

**Coil Form Type:**

Solid single component

**Winding Shielding Method:**

Internal shield grounded to core and brought out to terminal single component

**Overall Diameter:**

2.000 inches

**Maximum Operating Temp:**

175.0 degrees celsius

**Distance Between Mounting Facility Centers:**

1.312 inches single mounting facility single center group

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded stud single group

**Rating Method:**

Winding turns single component all secondary

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thread Size:**

0.164 inches single group

**Winding Conductor Size:**

0.02257 inches american wire gage single component 2nd secondary

**Test Data Document:**

80063-sc-c-64149 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

8 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0