## NSN 5950-00-221-0653

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-221-0653

| Reliability Indicator:  |
|---|
| Not established   |
| Overall Length:   |
| 2.313 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Length:   |
| 1.734 inches single mounting facility single center group and 1.766 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 1.609 inches single mounting facility single center group and 1.641 inches single mounting facility single center group |
| Overall Height:   |
| Between 2.734 inches and 2.766 inches   |
| Overall Width:  |
| Between 2.047 inches and 2.079 inches   |
| Mounting Hole Diameter:   |
| 0.172 inches single group and 0.204 inches single group   |
| Inductance Type:  |
| Swinging  |
| Inductance Rating:  |
| 22.00 millihenries single component single winding and 50.00 millihenries single component single winding               |
| Frequency Rating:   |
| 45.0 hertz single component and 440.0 hertz single component  |
| Maximum Operating Temp:   |
| 130.0 degrees celsius   |
| Winding Quantity:   |
| 1 single component  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Quantity:   |
| 4 single group  |
| Mounting Method:  |
| Unthreaded hole single group  |
| Rating Method:  |
| Electrical single component single winding  |
| Winding Operating Current:  |
| 1.0 amperes dc single component single winding and 2.25 amperes dc single component single winding                      |
| Terminal Type And Quantity:   |
| 2 tab, solder lug   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |

No

## NSN 5950-00-221-0653

Reactor - Page 2 of 2



Fiig:

A058b0