NSN 5950-00-221-0653

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-221-0653

| Reliability Indicator: |
|---|
| Not established |
| Overall Length: |
| 2.313 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.734 inches single mounting facility single center group and 1.766 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.609 inches single mounting facility single center group and 1.641 inches single mounting facility single center group |
| Overall Height: |
| Between 2.734 inches and 2.766 inches |
| Overall Width: |
| Between 2.047 inches and 2.079 inches |
| Mounting Hole Diameter: |
| 0.172 inches single group and 0.204 inches single group |
| Inductance Type: |
| Swinging |
| Inductance Rating: |
| 22.00 millihenries single component single winding and 50.00 millihenries single component single winding |
| Frequency Rating: |
| 45.0 hertz single component and 440.0 hertz single component |
| Maximum Operating Temp: |
| 130.0 degrees celsius |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Rating Method: |
| Electrical single component single winding |
| Winding Operating Current: |
| 1.0 amperes dc single component single winding and 2.25 amperes dc single component single winding |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5950-00-221-0653

Reactor - Page 2 of 2



Fiig:

A058b0