

View Online at <https://aerobasegroup.com/nsn/5950-00-221-8229>

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

5.562 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component and 425.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

6.719 inches

**Body Width:**

5.188 inches

**Body Height:**

6.812 inches

**Inclosure Type:**

Hermetically sealed with oil

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 6 secondary single component

**Thready Qty Per Inch (tpi):**

16 single group

**Thread Size:**

0.375 inches single group

**Special Features:**

Case metal material, o/a h of terminals, fourteen at 0.469 in., two at 1.781 in., one at 2.078 in., primary winding rated 125 v w/taps at 105 v and 115 v, secondary windings rated 2.5 v at 3 amp, 5.1 v at 3 amp, 5.4 v at 8 amp, 6.4 v at 10.3 amp, 650 v at 175 ma w/center tap, 5 kv at 5 ma

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

17 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0