

View Online at <https://aerobasegroup.com/nsn/5950-00-221-8229>

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.562 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 425.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

6.719 inches

Body Width:

5.188 inches

Body Height:

6.812 inches

Inclosure Type:

Hermetically sealed with oil

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 6 secondary single component

Thready Qty Per Inch (tpi):

16 single group

Thread Size:

0.375 inches single group

Special Features:

Case metal material, o/a h of terminals, fourteen at 0.469 in., two at 1.781 in., one at 2.078 in., primary winding rated 125 v w/taps at 105 v and 115 v, secondary windings rated 2.5 v at 3 amp, 5.1 v at 3 amp, 5.4 v at 8 amp, 6.4 v at 10.3 amp, 650 v at 175 ma w/center tap, 5 kv at 5 ma

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

17 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0