

View Online at <https://aerobasegroup.com/nsn/5950-00-222-7749>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.300 inches single mounting facility single center group and 2.360 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.970 inches single mounting facility single center group and 2.030 inches single mounting facility single center group

Mounting Slot Width:

0.150 inches single group and 0.210 inches single group

Frequency Rating:

50.0 hertz single component and 1.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internally shielded single component

Body Length:

3.310 inches

Body Width:

2.630 inches

Body Height:

3.130 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Winding Operating Current:

261.0 milliamperes ac single component 1st secondary

Winding Power Rating:

30.0 volts-amperes single component 1st secondary

Winding Operating Voltage:

26.00 ac pounds per hour wet single component 2nd secondary

Terminal Type And Quantity:

8 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0