NSN 5950-00-222-7749

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-222-7749

View Online at https://aerobasegroup.com/nsn/5950-00-222-7749
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.300 inches single mounting facility single center group and 2.360 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.970 inches single mounting facility single center group and 2.030 inches single mounting facility single center group
Mounting Slot Width:
0.150 inches single group and 0.210 inches single group
Frequency Rating:
50.0 hertz single component and 1.0 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Winding Shielding Method:
Internally shielded single component
Body Length:
3.310 inches
Body Width:
2.630 inches
Body Height:
3.130 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Slot single group
Winding Function And Quantity:
2 primary single component and 2 secondary single component
Winding Operating Current:
261.0 milliamperes ac single component 1st secondary
Winding Power Rating:
30.0 volts-amperes single component 1st secondary
Winding Operating Voltage:
26.00 ac pounds per hour wet single component 2nd secondary
Terminal Type And Quantity:
8 wire lead
Shelf Life:
N/a
Unit Of Measure:
<u></u>

No

Demilitarization:

NSN 5950-00-222-7749

Power Transformer - Page 2 of 2



Fiig:

A058b0