NSN 5950-00-223-1832

Reactor-transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-223-1832

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.813 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.641 inches single mounting facility single center group

Inductance Rating:

46.00 henry single component single winding

Frequency Rating:

48.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Primary To Secondary Turn Ratio:

1 to 5 single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.031 inches

Body Width:

2.031 inches

Body Height:

3.969 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component single winding

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

10.0 milliamperes dc single component single winding

Dc Resistance Rating In Ohms:

1550.000 single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

5 standoff, solder lug

NSN 5950-00-223-1832

Reactor-transformer - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0