## NSN 5950-00-224-2055

Electrical Coil - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-224-2055

Not established Turn Quantity: 12600 single component single winding Mounting Hole Diameter: 1.000 inches single group Body Length: 2.188 inches Body Outside Diameter: 3.125 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01003 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 690.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a Unit Of Measure:	Reliability Indicator:
Mounting Hole Diameter:  1.000 inches single group  Body Length:  2.188 inches  Body Outside Diameter:  3.125 inches  Winding Quantity:  1 single component Inclosure Type: Fully enclosed  Mounting Facility Quantity:  1 single group  Mounting Method: Unthreaded hole single group  Rating Method: Electrical single component single winding and winding turns single component single winding  Winding Conductor Size:  0.01003 inches american wire gage single component single winding  Dc Resistance Rating In Ohms:  690.000 single component single winding  Winding Operating Voltage:  115.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 threaded stud  Shelf Life:  N/a	Not established
Mounting Hole Diameter:  1.000 inches single group  Body Length:  2.188 inches  Body Outside Diameter:  3.125 inches  Winding Quantity:  1 single component  Inclosure Type:  Fully enclosed  Mounting Facility Quantity:  1 single group  Mounting Method:  Unthreaded hole single group  Rating Method:  Electrical single component single winding and winding turns single component single winding  Winding Conductor Size:  0.01003 inches american wire gage single component single winding  Dc Resistance Rating In Ohms:  690.000 single component single winding  Winding Operating Voltage:  115.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 threaded stud  Shelf Life:  N/a	Turn Quantity:
Body Length: 2.188 inches Body Outside Diameter: 3.125 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01003 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 690.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a	12600 single component single winding
Body Length:  2.188 inches  Body Outside Diameter:  3.125 inches  Winding Quantity:  1 single component Inclosure Type: Fully enclosed  Mounting Facility Quantity:  1 single group  Mounting Method: Unthreaded hole single group  Rating Method: Electrical single component single winding and winding turns single component single winding  Winding Conductor Size:  0.01003 inches american wire gage single component single winding  Dc Resistance Rating In Ohms:  690.000 single component single winding  Winding Operating Voltage:  115.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 threaded stud  Shelf Life: N/a	Mounting Hole Diameter:
2.188 inches  Body Outside Diameter: 3.125 inches  Winding Quantity: 1 single component Inclosure Type: Fully enclosed  Mounting Facility Quantity: 1 single group  Mounting Method: Unthreaded hole single group  Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01003 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 690.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a	1.000 inches single group
Body Outside Diameter: 3.125 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01003 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 690.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a	Body Length:
3.125 inches Winding Quantity: 1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01003 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 690.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a	2.188 inches
Winding Quantity:  1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity:  1 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size:  0.01003 inches american wire gage single component single winding Dc Resistance Rating In Ohms:  690.000 single component single winding Winding Operating Voltage:  115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity:  2 threaded stud Shelf Life: N/a	Body Outside Diameter:
1 single component Inclosure Type: Fully enclosed Mounting Facility Quantity: 1 single group Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01003 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 690.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a	3.125 inches
Inclosure Type: Fully enclosed  Mounting Facility Quantity: 1 single group  Mounting Method: Unthreaded hole single group  Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01003 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 690.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a	Winding Quantity:
Fully enclosed  Mounting Facility Quantity:  1 single group  Mounting Method: Unthreaded hole single group  Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size:  0.01003 inches american wire gage single component single winding  Dc Resistance Rating In Ohms:  690.000 single component single winding  Winding Operating Voltage:  115.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 threaded stud  Shelf Life:  N/a	1 single component
Mounting Facility Quantity:  1 single group  Mounting Method: Unthreaded hole single group  Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size:  0.01003 inches american wire gage single component single winding  Dc Resistance Rating In Ohms:  690.000 single component single winding  Winding Operating Voltage:  115.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 threaded stud  Shelf Life:  N/a	Inclosure Type:
1 single group  Mounting Method: Unthreaded hole single group  Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01003 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 690.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a	Fully enclosed
Mounting Method: Unthreaded hole single group Rating Method: Electrical single component single winding and winding turns single component single winding Winding Conductor Size: 0.01003 inches american wire gage single component single winding Dc Resistance Rating In Ohms: 690.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a	Mounting Facility Quantity:
Unthreaded hole single group  Rating Method:  Electrical single component single winding and winding turns single component single winding  Winding Conductor Size:  0.01003 inches american wire gage single component single winding  Dc Resistance Rating In Ohms:  690.000 single component single winding  Winding Operating Voltage:  115.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 threaded stud  Shelf Life:  N/a	1 single group
Rating Method:  Electrical single component single winding and winding turns single component single winding Winding Conductor Size:  0.01003 inches american wire gage single component single winding  Dc Resistance Rating In Ohms: 690.000 single component single winding  Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity: 2 threaded stud  Shelf Life:  N/a	Mounting Method:
Electrical single component single winding and winding turns single component single winding  Winding Conductor Size:  0.01003 inches american wire gage single component single winding  Dc Resistance Rating In Ohms:  690.000 single component single winding  Winding Operating Voltage:  115.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 threaded stud  Shelf Life:  N/a	Unthreaded hole single group
Winding Conductor Size:  0.01003 inches american wire gage single component single winding  Dc Resistance Rating In Ohms:  690.000 single component single winding  Winding Operating Voltage:  115.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 threaded stud  Shelf Life:  N/a	Rating Method:
0.01003 inches american wire gage single component single winding  Dc Resistance Rating In Ohms: 690.000 single component single winding  Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity: 2 threaded stud  Shelf Life: N/a	Electrical single component single winding and winding turns single component single winding
Dc Resistance Rating In Ohms: 690.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a	Winding Conductor Size:
690.000 single component single winding Winding Operating Voltage: 115.00 dc pounds per hour wet single component single winding Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a	0.01003 inches american wire gage single component single winding
Winding Operating Voltage:  115.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 threaded stud  Shelf Life:  N/a	Dc Resistance Rating In Ohms:
115.00 dc pounds per hour wet single component single winding  Terminal Type And Quantity:  2 threaded stud  Shelf Life:  N/a	690.000 single component single winding
Terminal Type And Quantity: 2 threaded stud Shelf Life: N/a	Winding Operating Voltage:
2 threaded stud  Shelf Life: N/a	115.00 dc pounds per hour wet single component single winding
Shelf Life: N/a	Terminal Type And Quantity:
N/a	2 threaded stud
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:
Demilitarization:	Demilitarization:
No	No
	Fiig:
Fiig:	A058b0
Fiig:	_
_	