NSN 5950-00-224-4483

Audio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-224-4483

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 1.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 1.750 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.188 inches single group |
| Transformer Function: |
| Line |
| Impedance Rating In Ohms: |
| 40.0 single component all secondary |
| Frequency Rating: |
| 16.0 kilohertz single component and 45.0 kilohertz single component |
| Maximum Transformer Power Rating: |
| 150.0 watts single component |
| Primary To Secondary Turn Ratio: |
| 1 to 9 single component |
| Winding Shielding Method: |
| Internal shield brought out to terminal single component |
| Body Length: |
| 2.625 inches |
| Body Width: |
| 1.750 inches |
| Body Height: |
| 3.812 inches |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Flange single group and unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 2 secondary single component |
| Terminal Type And Quantity: |
| 8 solder stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5950-00-224-4483

Audio Frequency Transformer - Page 2 of 2



Fiig:

A058b0