

View Online at <https://aerobasegroup.com/nsn/5950-00-227-5828>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Fungus proof and airtight and moisture resistant and vibration resistant

Overall Length:

1.270 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.108 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Width:

1.160 inches

Body Height:

0.900 inches

Maximum Operating Temp:

130.0 degrees celsius

Mounting Tab Width:

0.175 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Tab single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Voltage:

2.20 ac volts single component single secondary and 12.30 ac volts single component single secondary and 26.30 ac volts single component single secondary and 36.40 ac volts single component single secondary and 38.60 ac volts single component single secondary

Special Features:

Output is connected to a fullwave rectified bridge for testing purposes

Test Data Document:

89944-71010179 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

9 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0