

View Online at <https://aerobasegroup.com/nsn/5950-00-227-5828>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Fungus proof and airtight and moisture resistant and vibration resistant

**Overall Length:**

1.270 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.108 inches single mounting facility single center group

**Frequency Rating:**

400.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and core single component

**Body Width:**

1.160 inches

**Body Height:**

0.900 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Mounting Tab Width:**

0.175 inches

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Tab single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Voltage:**

2.20 ac volts single component single secondary and 12.30 ac volts single component single secondary and 26.30 ac volts single component single secondary and 36.40 ac volts single component single secondary and 38.60 ac volts single component single secondary

**Special Features:**

Output is connected to a fullwave rectified bridge for testing purposes

**Test Data Document:**

89944-71010179 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

9 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0