NSN 5950-00-227-7833

Audio Frequency Transformer - Page 1 of 2



To Length:

To Width:

| View Online at https://aerobasegroup.com/nsn/5950-00-227-7833 |
|---|
| Reliability Indicator: |
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel |
| 1.062 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel |
| 1.062 inches single mounting facility single center group |
| Transformer Function: |
| Line |
| Impedance Rating In Ohms: |
| 600.0 single component single secondary |
| Frequency Rating: |
| 200.0 hertz single component and 3.5 kilohertz single component |
| Maximum Transformer Power Rating: |
| 20.0 milliwatts single component |
| Body Length: |
| 1.500 inches |
| Body Width: |
| 1.500 inches |
| Body Height: |
| 2.250 inches |
| Inclosure Type: |
| Hermetically sealed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 35.0 milliamperes dc single component single primary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 4 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5950-00-227-7833

Audio Frequency Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0