NSN 5950-00-228-0776

Audio Frequency Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-228-0776

Reliability Indicator: Not established Center To Center Distance Between Mounting Facilities Parallel To Length: 1.698 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.625 inches single mounting facility single center group Transformer Function: Line Impedance Rating In Ohms: 125.0 single component all primary Primary To Secondary Turn Ratio: 1 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 3.250 inches Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity: 12 tab, solder lug
Center To Center Distance Between Mounting Facilities Parallel To Length: 1.688 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.625 inches single mounting facility single center group Transformer Function: Line Impedance Rating In Ohms: 125.0 single component all primary Primary To Secondary Turn Ratio: 1 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 3.250 inches Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
1.688 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 2.625 inches single mounting facility single center group Transformer Function: Line Impedance Rating In Ohms: 125.0 single component all primary Primary To Secondary Turn Ratio: 1 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 3.250 inches Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Center To Center Distance Between Mounting Facilities Parallel To Width: 2.625 inches single mounting facility single center group Transformer Function: Line Impedance Rating In Ohms: 125.0 single component all primary Primary To Secondary Turn Ratio: 1 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 3.250 inches Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
2.625 inches single mounting facility single center group Transformer Function: Line Impedance Rating In Ohms: 125.0 single component all primary Primary To Secondary Turn Ratio: 1 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 3.250 inches Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Transformer Function: Line Impedance Rating In Ohms: 125.0 single component all primary Primary To Secondary Turn Ratio: 1 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 3.250 inches Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Line Impedance Rating In Ohms: 125.0 single component all primary Primary To Secondary Turn Ratio: 1 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 3.250 inches Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Impedance Rating In Ohms: 125.0 single component all primary Primary To Secondary Turn Ratio: 1 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 3.250 inches Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Primary To Secondary Turn Ratio: 1 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 3.250 inches Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Primary To Secondary Turn Ratio: 1 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 3.250 inches Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
1 to 1 single component Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 3.250 inches Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Winding Shielding Method: Internal shield grounded to inclosure single component Body Length: 3.250 inches Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Internal shield grounded to inclosure single component Body Length: 3.250 inches Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Body Length: 3.250 inches Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
3.250 inches Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Body Width: 2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
2.625 inches Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Body Height: 3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
3.188 inches Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Inclosure Type: Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Partially enclosed, double shell Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Mounting Facility Quantity: 4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
4 single group Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Mounting Method: Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Flange single group and unthreaded hole single group Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
Winding Function And Quantity: 2 primary single component and 2 secondary single component Terminal Type And Quantity:
2 primary single component and 2 secondary single component Terminal Type And Quantity:
Terminal Type And Quantity:
•
12 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Demilitarization: No