

View Online at <https://aerobasegroup.com/nsn/5950-00-228-5863>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Vibration resistant

**Inductance Rating:**

150.00 microhenries single component single winding

**Coil Form Type:**

Solid single component

**Core Construction:**

Powdered single component

**Body Length:**

Between 0.365 inches and 0.385 inches

**Body Outside Diameter:**

Between 0.146 inches and 0.166 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Rating Method:**

Electrical single component single winding

**Features Provided:**

Tinned wire leads

**Winding Conductor Size:**

0.02535 inches american wire gage single component single winding

**Winding Operating Current:**

114.0 milliamperes dc single component single winding

**Dc Resistance Rating In Ohms:**

6.050 single component single winding

**Quality Factor:**

65 single component single winding

**Special Features:**

Suffix letter on p/n denotes standard tolerance of 5 pct

**Test Data Document:**

81349-mil-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 wire lead

**Specification Data:**

96906-ms90538 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0