NSN 5950-00-228-7184

Radio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-228-7184

| Reliability Indicator: |
|--|
| Not established |
| Turn Quantity: |
| 750 single component single primary |
| Inductance Rating: |
| 6.65 millihenries single component single primary and 15.56 millihenries single component single primary |
| Frequency Rating: |
| 82.0 kilohertz single component |
| Coil Form Type: |
| Hollow single component |
| Adjustment Device Drive Type: |
| Slotted screw single component |
| Body Length: |
| 2.188 inches |
| Body Outside Diameter: |
| 1.250 inches |
| Distance Between Mounting Facility Centers: |
| 0.875 inches single mounting facility single center group |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 2 single group |
| Mounting Method: |
| Threaded hole single group |
| Rating Method: |
| Electrical single component single primary and winding turns single component single primary |
| Winding Function And Quantity: |
| 1 primary single component |
| Thready Qty Per Inch (tpi): |
| 32 single group |
| Thread Size: |
| 0.138 inches single group |
| Winding Conductor Size: |
| 0.00397 inches american wire gage single component single primary |
| Adjustment Method And Quantity: |
| 1 adjustable core single component |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |

N/a

3 tab, solder lug

Shelf Life:

NSN 5950-00-228-7184

Radio Frequency Transformer - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

--

Demilitarization:

No

Fiig:

A058b0