

View Online at <https://aerobasegroup.com/nsn/5950-00-229-5105>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.000 inches single mounting facility single center group

Transformer Function:

Line

Impedance Rating In Ohms:

1000.0 single component single primary

Frequency Rating:

60.0 hertz single component

Maximum Transformer Power Rating:

6.0 milliwatts single component

Primary To Secondary Turn Ratio:

1 to 2 single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

Between 1.860 inches and 1.900 inches

Body Width:

Between 1.420 inches and 1.460 inches

Body Height:

Between 2.980 inches and 3.020 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Test Data Document:

06845-a-217126 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0