

View Online at <https://aerobasegroup.com/nsn/5950-00-230-1171>

**Reliability Indicator:**

Not established

**Impedance Rating In Ohms:**

50.0 single component single secondary and 500.0 single component single secondary

**Frequency Rating:**

50.0 hertz single component and 7.0 kilohertz single component

**Primary To Secondary Turn Ratio:**

1 to 1 to 11-55/64 single component

**Winding Shielding Method:**

Internal shield grounded to inclosure and brought out to terminal single component

**Body Length:**

1.750 inches

**Body Width:**

1.750 inches

**Body Height:**

3.500 inches

**Distance Between Mounting Facility Centers:**

0.875 inches single mounting facility single center group

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

2 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

2 primary single component and 1 secondary single component

**Thready Qty Per Inch (tpi):**

32 single group

**Thread Size:**

0.138 inches single group

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

8 standoff, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0