NSN 5950-00-230-6110

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-230-6110

Inductance Type: Fixed Inductance Rating: 25.00 henry single component single winding Body Length: 3.500 inches Body Width: 1.750 inches Body Height: 1.750 inches Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi): 32 single group
Inductance Rating: 25.00 henry single component single winding Body Length: 3.500 inches Body Width: 1.750 inches Body Height: 1.750 inches Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Inductance Rating: 25.00 henry single component single winding Body Length: 3.500 inches Body Width: 1.750 inches Body Height: 1.750 inches Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Body Length: 3.500 inches Body Width: 1.750 inches Body Height: 1.750 inches Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Body Length: 3.500 inches Body Width: 1.750 inches Body Height: 1.750 inches Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
3.500 inches Body Width: 1.750 inches Body Height: 1.750 inches Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Body Width: 1.750 inches Body Height: 1.750 inches Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
1.750 inches Body Height: 1.750 inches Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Body Height: 1.750 inches Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
1.750 inches Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Distance Between Mounting Facility Centers: 0.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
O.875 inches single mounting facility single center group Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Winding Quantity: 1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
1 single component Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Inclosure Type: Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Hermetically sealed Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Mounting Facility Quantity: 2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
2 single group Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Mounting Method: Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Threaded stud single group Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Rating Method: Electrical single component single winding Thready Qty Per Inch (tpi):
Electrical single component single winding Thready Qty Per Inch (tpi):
Thready Qty Per Inch (tpi):
32 single group
Thread Size:
0.138 inches single group
Winding Operating Current:
28.0 milliamperes dc single component single winding
Dc Resistance Rating In Ohms:
1100.000 single component single winding
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5950-00-230-6110

Reactor - Page 2 of 2



Fiig:

A058b0