

View Online at <https://aerobasegroup.com/nsn/5950-00-230-8419>

Reliability Indicator:

Not established

Overall Length:

Between 1.395 inches and 1.455 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.975 inches single mounting facility single center group and 1.005 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.165 inches single mounting facility single center group and 1.195 inches single mounting facility single center group

Overall Height:

Between 1.415 inches and 1.445 inches

Overall Width:

Between 1.225 inches and 1.285 inches

Mounting Hole Diameter:

0.111 inches single group and 0.121 inches single group

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

15.0 volt-ampere single component

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

750.0 milliamperes ac single component single secondary

Winding Operating Voltage:

20.00 ac volts single component single secondary

Terminal Type And Quantity:

5 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0