

View Online at <https://aerobasegroup.com/nsn/5950-00-230-8541>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.245 inches single mounting facility all center groupings and 1.255 inches single mounting facility all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.464 inches single mounting facility all center groupings and 1.474 inches single mounting facility all center groupings

Mounting Hole Diameter:

0.090 inches 2nd group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component

Winding Shielding Method:

Internal shield grounded to core single component

Body Length:

2.000 inches

Body Width:

1.875 inches

Body Height:

1.000 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Unthreaded hole all groupings

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

400.0 milliamperes dc single component all secondary

Winding Operating Voltage:

37.20 ac volts single component all secondary

Special Features:

All secondary center taps tied together and brought out to same terminal

Terminal Type And Quantity:

10 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0