## NSN 5950-00-231-1942

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-231-1942

Reliability Indicator:
Not established
Mounting Hole Diameter:
0.188 inches single group
Inductance Type:
Fixed
Inductance Rating:
3.80 henry single component single winding
Body Length:
2.844 inches
Body Width:
1.531 inches
Body Height:
1.656 inches
Distance Between Mounting Facility Centers:
1.250 inches single mounting facility single center group
Winding Quantity:
1 single component
Inclosure Type:
Open
Mounting Facility Quantity:
Mounting Facility Quantity.
2 single group
2 single group
2 single group  Mounting Method:
2 single group  Mounting Method:  Flange single group and unthreaded hole single group
2 single group  Mounting Method:  Flange single group and unthreaded hole single group  Rating Method:
2 single group  Mounting Method:  Flange single group and unthreaded hole single group  Rating Method:  Electrical single component single winding
2 single group  Mounting Method: Flange single group and unthreaded hole single group  Rating Method: Electrical single component single winding  Winding Operating Current:
2 single group  Mounting Method: Flange single group and unthreaded hole single group  Rating Method: Electrical single component single winding  Winding Operating Current:  105.0 milliamperes dc single component single winding
2 single group  Mounting Method: Flange single group and unthreaded hole single group  Rating Method: Electrical single component single winding  Winding Operating Current:  105.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:
2 single group  Mounting Method: Flange single group and unthreaded hole single group  Rating Method: Electrical single component single winding  Winding Operating Current: 105.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 200.000 single component single winding
2 single group  Mounting Method: Flange single group and unthreaded hole single group  Rating Method: Electrical single component single winding  Winding Operating Current: 105.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 200.000 single component single winding  Terminal Type And Quantity:
2 single group  Mounting Method: Flange single group and unthreaded hole single group  Rating Method: Electrical single component single winding  Winding Operating Current: 105.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 200.000 single component single winding  Terminal Type And Quantity: 2 tab, solder lug
2 single group  Mounting Method: Flange single group and unthreaded hole single group  Rating Method: Electrical single component single winding  Winding Operating Current: 105.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 200.000 single component single winding  Terminal Type And Quantity: 2 tab, solder lug  Shelf Life:
2 single group  Mounting Method: Flange single group and unthreaded hole single group  Rating Method: Electrical single component single winding  Winding Operating Current: 105.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 200.000 single component single winding  Terminal Type And Quantity: 2 tab, solder lug  Shelf Life: N/a
2 single group  Mounting Method: Flange single group and unthreaded hole single group  Rating Method: Electrical single component single winding  Winding Operating Current: 105.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 200.000 single component single winding  Terminal Type And Quantity: 2 tab, solder lug  Shelf Life: N/a
2 single group  Mounting Method: Flange single group and unthreaded hole single group  Rating Method: Electrical single component single winding  Winding Operating Current: 105.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms: 200.000 single component single winding  Terminal Type And Quantity: 2 tab, solder lug  Shelf Life: N/a  Unit Of Measure:
2 single group  Mounting Method: Flange single group and unthreaded hole single group  Rating Method: Electrical single component single winding  Winding Operating Current:  105.0 milliamperes dc single component single winding  Dc Resistance Rating In Ohms:  200.000 single component single winding  Terminal Type And Quantity:  2 tab, solder lug  Shelf Life:  N/a  Unit Of Measure:   Demilitarization: