NSN 5950-00-231-1981

Reactor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-231-1981

| Reliability Indicator: |
|---|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 3.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.750 inches single mounting facility single center group |
| Inductance Type: |
| Fixed |
| Inductance Rating: |
| 830.00 millihenries single component single winding |
| Body Length: |
| 4.500 inches |
| Body Width: |
| 5.000 inches |
| Body Height: |
| 5.000 inches |
| Winding Quantity: |
| 1 single component |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Rating Method: |
| Electrical single component single winding |
| Winding Operating Current: |
| 2.5 amperes dc single component single winding |
| Dc Resistance Rating In Ohms: |
| 0.800 single component single winding |
| Special Features: |
| Tapped at 0.011 ohms, 0.016 ohms, 0.023 ohms, 0.032 ohms, 0.071 ohms and 0.753 ohms |
| Terminal Type And Quantity: |
| 8 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |