

View Online at <https://aerobasegroup.com/nsn/5950-00-231-2003>

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component and 2.4 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.250 inches

Body Width:

3.000 inches

Body Height:

2.625 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component

Winding Power Rating:

62.0 volts-amperes single component single primary input

Winding Operating Voltage:

69.50 ac volts single component single primary output or 72.24 ac volts single component single primary output or 75.73 ac volts single component single primary output or 78.11 ac volts single component single primary output or 82.02 ac volts single component single primary output or 85.93 ac volts single component single primary output or 89.45 ac volts single component single primary output or 93.36 ac volts single component single primary output or 96.88 ac volts single component single primary output or 100.40 ac volts single component single primary output or 104.31 ac volts single component single primary output or 107.83 ac volts single component single primary output

Terminal Type And Quantity:

13 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0