## NSN 5950-00-231-4810

Reliability Indicator:

Not established

Audio Frequency Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-231-4810

Center To Center Distance Between Mounting Facilities Parallel To Width: 4.000 inches single mounting facility single center group Overall Height: 7.000 inches Impedance Rating In Ohms: 12500.0 single component single primary Frequency Rating: 12.0 kilohertz single component Primary To Secondary Turn Ratio: 1 to 7-3/4 single component Body Length: 5.250 inches Body Width: 5.000 inches Body Height: 5.000 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud	4.250 inches single mounting facility single center group  Center To Center Distance Between Mounting Facilities Parallel To Width: 4.000 inches single mounting facility single center group  Overall Height: 7.000 inches  Impedance Rating In Ohms: 12500.0 single component single primary  Frequency Rating: 12.0 kilohertz single component  Primary To Secondary Turn Ratio: 1 to 7-3/4 single component  Body Length: 5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud  Shelf Life: N/a	Center To Center Distance Between Mounting Facilities Parallel To Length:
4.000 inches single mounting facility single center group  Overall Height: 7.000 inches  Impedance Rating In Ohms: 12500.0 single component single primary  Frequency Rating: 12.0 kilohertz single component  Primary To Secondary Turn Ratio: 1 to 7-3/4 single component  Body Length: 5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud	4.000 inches single mounting facility single center group  Overall Height: 7.000 inches  Impedance Rating In Ohms: 12500.0 single component single primary  Frequency Rating: 12.0 kilohertz single component  Primary To Secondary Turn Ratio: 1 to 7-3/4 single component  Body Length: 5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud  Shelf Life:	4.250 inches single mounting facility single center group
Overall Height: 7.000 inches Impedance Rating In Ohms: 12500.0 single component single primary Frequency Rating: 12.0 kilohertz single component Primary To Secondary Turn Ratio: 1 to 7-3/4 single component Body Length: 5.250 inches Body Width: 5.000 inches Body Height: 5.000 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud	Overall Height: 7.000 inches Impedance Rating In Ohms: 12500.0 single component single primary Frequency Rating: 12.0 kilohertz single component Primary To Secondary Turn Ratio: 1 to 7-3/4 single component Body Length: 5.250 inches Body Width: 5.000 inches Body Height: 5.000 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud Shelf Life:	Center To Center Distance Between Mounting Facilities Parallel To Width:
Impedance Rating In Ohms:  12500.0 single component single primary  Frequency Rating:  12.0 kilohertz single component  Primary To Secondary Turn Ratio:  1 to 7-3/4 single component  Body Length:  5.250 inches  Body Width:  5.000 inches  Body Height:  5.000 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity:  4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity:  1 primary and 1 secondary single component  Thready Qty Per Inch (tpi):  40 single group  Winding Operating Current:  200.0 milliamperes dc single component single primary  Thread Series Designator:  Uns single group  Terminal Type And Quantity:  5 threaded stud	7.000 inches Impedance Rating In Ohms: 12500.0 single component single primary Frequency Rating: 12.0 kilohertz single component Primary To Secondary Turn Ratio: 1 to 7-3/4 single component Body Length: 5.250 inches Body Width: 5.000 inches Body Height: 5.000 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud Shelf Life:	4.000 inches single mounting facility single center group
Impedance Rating In Ohms:  12500.0 single component single primary  Frequency Rating:  12.0 kilohertz single component  Primary To Secondary Turn Ratio:  1 to 7-3/4 single component  Body Length:  5.250 inches  Body Width:  5.000 inches  Body Height:  5.000 inches  Inclosure Type:  Hermetically sealed  Mounting Facility Quantity:  4 single group  Mounting Method:  Threaded stud single group  Winding Function And Quantity:  1 primary and 1 secondary single component  Thready Qty Per Inch (tpi):  40 single group  Winding Operating Current:  200.0 milliamperes dc single component single primary  Thread Series Designator:  Uns single group  Terminal Type And Quantity:  5 threaded stud	Impedance Rating In Ohms:  12500.0 single component single primary  Frequency Rating:  12.0 kilohertz single component  Primary To Secondary Turn Ratio:  1 to 7-3/4 single component  Body Length: 5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud  Shelf Life:	Overall Height:
12500.0 single component single primary  Frequency Rating: 12.0 kilohertz single component  Primary To Secondary Turn Ratio: 1 to 7-3/4 single component  Body Length: 5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud	12500.0 single component single primary  Frequency Rating:  12.0 kilohertz single component  Primary To Secondary Turn Ratio:  1 to 7-3/4 single component  Body Length: 5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud  Shelf Life:	7.000 inches
Frequency Rating:  12.0 kilohertz single component  Primary To Secondary Turn Ratio:  1 to 7-3/4 single component  Body Length: 5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud	Frequency Rating:  12.0 kilohertz single component  Primary To Secondary Turn Ratio:  1 to 7-3/4 single component  Body Length: 5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Winding Operating Current: 200.0 milliamperes do single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud  Shelf Life:	Impedance Rating In Ohms:
12.0 kilohertz single component  Primary To Secondary Turn Ratio:  1 to 7-3/4 single component  Body Length: 5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.250 inches single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud	12.0 kilohertz single component  Primary To Secondary Turn Ratio:  1 to 7-3/4 single component  Body Length: 5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.250 inches single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud  Shelf Life:	12500.0 single component single primary
Primary To Secondary Turn Ratio:  1 to 7-3/4 single component  Body Length: 5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud	Primary To Secondary Turn Ratio:  1 to 7-3/4 single component  Body Length: 5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.250 inches single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud  Shelf Life:	Frequency Rating:
1 to 7-3/4 single component  Body Length: 5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud	1 to 7-3/4 single component  Body Length: 5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.250 inches single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud  Shelf Life:	12.0 kilohertz single component
Body Length: 5.250 inches Body Width: 5.000 inches Body Height: 5.000 inches Body Height: 5.000 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud	Body Length: 5.250 inches Body Width: 5.000 inches Body Height: 5.000 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud Shelf Life:	Primary To Secondary Turn Ratio:
5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.250 inches single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud	5.250 inches  Body Width: 5.000 inches  Body Height: 5.000 inches  Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.250 inches single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud  Shelf Life:	1 to 7-3/4 single component
Body Width: 5.000 inches Body Height: 5.000 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud	Body Width: 5.000 inches Body Height: 5.000 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud Shelf Life:	Body Length:
5.000 inches  Body Height: 5.000 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud	5.000 inches  Body Height: 5.000 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud Shelf Life:	5.250 inches
Body Height: 5.000 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud	Body Height: 5.000 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud Shelf Life:	Body Width:
Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud	5.000 inches Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud Shelf Life:	5.000 inches
Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud	Inclosure Type: Hermetically sealed Mounting Facility Quantity: 4 single group Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud Shelf Life:	Body Height:
Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.250 inches single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator:  Uns single group  Terminal Type And Quantity: 5 threaded stud	Hermetically sealed  Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.250 inches single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud  Shelf Life:	5.000 inches
Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.250 inches single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud	Mounting Facility Quantity: 4 single group  Mounting Method: Threaded stud single group  Winding Function And Quantity: 1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.250 inches single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud  Shelf Life:	Inclosure Type:
Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud	Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud Shelf Life:	Hermetically sealed
Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud	Mounting Method: Threaded stud single group Winding Function And Quantity: 1 primary and 1 secondary single component Thready Qty Per Inch (tpi): 40 single group Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud Shelf Life:	Mounting Facility Quantity:
Threaded stud single group  Winding Function And Quantity:  1 primary and 1 secondary single component  Thready Qty Per Inch (tpi):  40 single group  Thread Size:  0.250 inches single group  Winding Operating Current:  200.0 milliamperes dc single component single primary  Thread Series Designator:  Uns single group  Terminal Type And Quantity:  5 threaded stud	Threaded stud single group  Winding Function And Quantity:  1 primary and 1 secondary single component  Thready Qty Per Inch (tpi):  40 single group  Thread Size:  0.250 inches single group  Winding Operating Current:  200.0 milliamperes dc single component single primary  Thread Series Designator:  Uns single group  Terminal Type And Quantity:  5 threaded stud  Shelf Life:	4 single group
Winding Function And Quantity:  1 primary and 1 secondary single component  Thready Qty Per Inch (tpi):  40 single group  Thread Size:  0.250 inches single group  Winding Operating Current:  200.0 milliamperes dc single component single primary  Thread Series Designator:  Uns single group  Terminal Type And Quantity:  5 threaded stud	Winding Function And Quantity:  1 primary and 1 secondary single component  Thready Qty Per Inch (tpi):  40 single group  Thread Size:  0.250 inches single group  Winding Operating Current:  200.0 milliamperes dc single component single primary  Thread Series Designator:  Uns single group  Terminal Type And Quantity:  5 threaded stud  Shelf Life:	Mounting Method:
1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.250 inches single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud	1 primary and 1 secondary single component  Thready Qty Per Inch (tpi): 40 single group  Thread Size: 0.250 inches single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud  Shelf Life:	Threaded stud single group
Thready Qty Per Inch (tpi):  40 single group  Thread Size:  0.250 inches single group  Winding Operating Current:  200.0 milliamperes dc single component single primary  Thread Series Designator:  Uns single group  Terminal Type And Quantity:  5 threaded stud	Thready Qty Per Inch (tpi):  40 single group  Thread Size:  0.250 inches single group  Winding Operating Current:  200.0 milliamperes dc single component single primary  Thread Series Designator:  Uns single group  Terminal Type And Quantity:  5 threaded stud  Shelf Life:	Winding Function And Quantity:
Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud	Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud Shelf Life:	1 primary and 1 secondary single component
Thread Size: 0.250 inches single group Winding Operating Current: 200.0 milliamperes dc single component single primary Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud	Thread Size:  0.250 inches single group  Winding Operating Current:  200.0 milliamperes dc single component single primary  Thread Series Designator:  Uns single group  Terminal Type And Quantity:  5 threaded stud  Shelf Life:	Thready Qty Per Inch (tpi):
0.250 inches single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud	0.250 inches single group  Winding Operating Current: 200.0 milliamperes dc single component single primary  Thread Series Designator: Uns single group  Terminal Type And Quantity: 5 threaded stud  Shelf Life:	40 single group
Winding Operating Current:  200.0 milliamperes dc single component single primary  Thread Series Designator:  Uns single group  Terminal Type And Quantity:  5 threaded stud	Winding Operating Current:  200.0 milliamperes dc single component single primary  Thread Series Designator:  Uns single group  Terminal Type And Quantity:  5 threaded stud  Shelf Life:	Thread Size:
200.0 milliamperes dc single component single primary  Thread Series Designator:  Uns single group  Terminal Type And Quantity:  5 threaded stud	200.0 milliamperes dc single component single primary  Thread Series Designator:  Uns single group  Terminal Type And Quantity:  5 threaded stud  Shelf Life:	0.250 inches single group
Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud	Thread Series Designator: Uns single group Terminal Type And Quantity: 5 threaded stud Shelf Life:	Winding Operating Current:
Uns single group  Terminal Type And Quantity: 5 threaded stud	Uns single group  Terminal Type And Quantity: 5 threaded stud  Shelf Life:	200.0 milliamperes dc single component single primary
Terminal Type And Quantity: 5 threaded stud	Terminal Type And Quantity: 5 threaded stud Shelf Life:	Thread Series Designator:
5 threaded stud	5 threaded stud Shelf Life:	Uns single group
	Shelf Life:	Terminal Type And Quantity:
Shelf Life:		5 threaded stud
	N/a	Shelf Life:
N/a		N/a
Unit Of Measure	Unit Of Measure:	Unit Of Measure:

## NSN 5950-00-231-4810

Audio Frequency Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0