

View Online at <https://aerobasegroup.com/nsn/5950-00-232-2383>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.250 inches single mounting facility single center group

Inductance Type:

Fixed

Inductance Rating:

2.00 henry single component single winding

Frequency Rating:

60.0 hertz single component

Body Length:

1.875 inches

Body Width:

1.750 inches

Body Height:

2.188 inches

Winding Quantity:

1 single component

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Rating Method:

Electrical single component single winding

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

165.0 milliamperes dc single component single winding

Dc Resistance Rating In Ohms:

90.000 single component single winding

Criticality Code Justification:

Feat

Special Features:

Item must comply with requirements of defense electronics supply center production standard no. L01275

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

2 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0