

View Online at <https://aerobasegroup.com/nsn/5950-00-233-3367>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

11.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

9.000 inches single mounting facility single center group

**Mounting Hole Diameter:**

0.625 inches single group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

50.0 kilovolt-ampere single component

**Body Length:**

31.500 inches

**Body Width:**

18.312 inches

**Body Height:**

17.375 inches

**End Application:**

Wsd: nimitz class cvn; austin ship class lpd-4 amphibious transport docks; forrestal class cv; hayes class t-ag 195

**Inclosure Type:**

Open

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group and unthreaded hole single group

**Cooling Type:**

Fins

**Cooling Method:**

Self-cooled

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Criticality Code Justification:**

Feat

**Winding Operating Voltage:**

450.00 ac volts single component single primary

**Special Features:**

Shock proof; weapon system essential

**Terminal Type And Quantity:**

4 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0