

View Online at <https://aerobasegroup.com/nsn/5950-00-233-3367>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

11.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

9.000 inches single mounting facility single center group

Mounting Hole Diameter:

0.625 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

50.0 kilovolt-ampere single component

Body Length:

31.500 inches

Body Width:

18.312 inches

Body Height:

17.375 inches

End Application:

Wsd: nimitz class cvn; austin ship class lpd-4 amphibious transport docks; forrestal class cv; hayes class t-ag 195

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Cooling Type:

Fins

Cooling Method:

Self-cooled

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Criticality Code Justification:

Feat

Winding Operating Voltage:

450.00 ac volts single component single primary

Special Features:

Shock proof; weapon system essential

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0