

View Online at <https://aerobasegroup.com/nsn/5950-00-233-3560>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

4.500 inches

Body Width:

2.812 inches

Body Height:

4.000 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component

Winding Tap Location (non-core):

Tap w/o center tap single component single secondary

Winding Operating Current:

790.0 milliamperes ac single component single primary output

Winding Power Rating:

91.0 volts-amperes single component single primary input

Winding Operating Voltage:

230.00 ac pounds per hour wet single component single primary input

Special Features:

Case metal material, o/h of terminals 0.438 in.

Terminal Type And Quantity:

3 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0