

View Online at <https://aerobasegroup.com/nsn/5950-00-233-7244>

**Reliability Indicator:**

Not established

**Overall Length:**

7.120 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.625 inches 2nd mounting facili type 2nd center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.625 inches 2nd mounting facili type 2nd center group

**Overall Height:**

5.620 inches

**Overall Width:**

5.000 inches

**Mounting Hole Diameter:**

0.250 inches 1st group

**Mounting Slot Width:**

0.250 inches 2nd group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Adjustment Device Drive Type:**

Shaft single component

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 2nd group

**Mounting Method:**

Unthreaded hole 1st group

**Winding Function And Quantity:**

1 primary, variable autotransformer type single component

**Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triangle:**

4.380 inches 1st mounting facili type 1st center group

**Winding Operating Current:**

10.0 amperes ac single component single primary output

**Winding Power Rating:**

1.4 kilovolt-amperes single component single primary output

**Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:**

4.380 inches 1st mounting facili type 1st center group

**Adjustment Method And Quantity:**

1 adjustable control single component

**Winding Operating Voltage:**

120.00 ac volts single component single primary input

**Terminal Type And Quantity:**

5 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0