

View Online at <https://aerobasegroup.com/nsn/5950-00-233-7244>

Reliability Indicator:

Not established

Overall Length:

7.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.625 inches 2nd mounting facili type 2nd center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.625 inches 2nd mounting facili type 2nd center group

Overall Height:

5.620 inches

Overall Width:

5.000 inches

Mounting Hole Diameter:

0.250 inches 1st group

Mounting Slot Width:

0.250 inches 2nd group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Adjustment Device Drive Type:

Shaft single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 2nd group

Mounting Method:

Unthreaded hole 1st group

Winding Function And Quantity:

1 primary, variable autotransformer type single component

Center To Center Distance Between Mounting Facilities Parallel To The Base Of An Isosceles Triangle:

4.380 inches 1st mounting facili type 1st center group

Winding Operating Current:

10.0 amperes ac single component single primary output

Winding Power Rating:

1.4 kilovolt-amperes single component single primary output

Center To Center Distance Between Mounting Facilities Parallel To The Altitude Of An Isosceles Triangle:

4.380 inches 1st mounting facili type 1st center group

Adjustment Method And Quantity:

1 adjustable control single component

Winding Operating Voltage:

120.00 ac volts single component single primary input

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0