

View Online at <https://aerobasegroup.com/nsn/5950-00-235-2614>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.750 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.000 inches single mounting facility single center group

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

5.000 inches

**Body Width:**

4.375 inches

**Body Height:**

5.125 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Thread Qty Per Inch (tpi):**

20 single group

**Thread Size:**

0.250 inches single group

**Winding Operating Voltage:**

125.00 ac volts single component single primary 2.30 ac volts single component single secondary and 4.50 ac volts single component single secondary and 6.80 ac volts single component single secondary and 9.00 ac volts single component single secondary and 11.20 ac volts single component single secondary and 13.40 ac volts single component single secondary and 15.60 ac volts single component single secondary and 17.80 ac volts single component single secondary and 20.00 ac volts single component single secondary and 22.30 ac volts single component single secondary and 49.00 ac volts single component single secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

15 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**