

View Online at <https://aerobasegroup.com/nsn/5950-00-235-2614>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

5.000 inches

Body Width:

4.375 inches

Body Height:

5.125 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

20 single group

Thread Size:

0.250 inches single group

Winding Operating Voltage:

125.00 ac volts single component single primary 2.30 ac volts single component single secondary and 4.50 ac volts single component single secondary and 6.80 ac volts single component single secondary and 9.00 ac volts single component single secondary and 11.20 ac volts single component single secondary and 13.40 ac volts single component single secondary and 15.60 ac volts single component single secondary and 17.80 ac volts single component single secondary and 20.00 ac volts single component single secondary and 22.30 ac volts single component single secondary and 49.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

15 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: