

View Online at <https://aerobasegroup.com/nsn/5950-00-235-2625>

**Reliability Indicator:**

Not establishednot established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

5.875 inches single mounting facility single center group5.875 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.875 inches single mounting facility single center group3.875 inches single mounting facility single center group

**Frequency Rating:**

60.0 hertz single component60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single componentsingle phase to single phase single component

**Body Length:**

6.625 inches 6.625 inches

**Body Width:**

4.625 inches 4.625 inches

**Body Height:**

6.750 inches 6.750 inches

**Inclosure Type:**

Hermetically sealedhermetically sealed

**Mounting Facility Quantity:**

4 single group4 single group

**Mounting Method:**

Threaded stud single groupthreaded stud single group

**Winding Function And Quantity:**

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

**Thready Qty Per Inch (tpi):**

20 single group20 single group

**Thread Size:**

0.250 inches single group0.250 inches single group

**Winding Operating Current:**

60.0 milliamperes ac single component 2nd secondary

**Winding Operating Voltage:**

4.00 ac volts single component 2nd secondary

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

8 standoff insulator

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0