

View Online at <https://aerobasegroup.com/nsn/5950-00-235-3786>

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.625 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches single mounting facility single center group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

6.688 inches

Body Width:

5.156 inches

Body Height:

6.438 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 5 secondary single component

Thready Qty Per Inch (tpi):

18 single group

Thread Size:

0.312 inches single group

Special Features:

Case metal material, primary windings rated 120 v and 120 v, secondary windings rated 5 v at 6 amp w/center tap, 10.2 v at 5 at 5 amp w/tap at 3.7 v, 15 v at 20 ma, 374 v at 30 ma, 470 v at 450 ma w/center tap and tapped at at 210 v and 260 v

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

19 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0