NSN 5950-00-235-6531

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-235-6531

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.250 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
4.500 inches single mounting facility single center group
Inductance Type:
Fixed
Inductance Rating:
7.50 henry single component all winding
Body Length:
7.406 inches
Body Width:
5.656 inches
Body Height:
8.531 inches
Winding Quantity:
2 single component
Inclosure Type:
Hermetically sealed
Mounting Facility Quantity:
4 single group
4 single group Mounting Method:
Mounting Method:
Mounting Method: Threaded stud single group
Mounting Method: Threaded stud single group Rating Method:
Mounting Method: Threaded stud single group Rating Method: Electrical single component all winding
Mounting Method: Threaded stud single group Rating Method: Electrical single component all winding Thready Qty Per Inch (tpi):
Mounting Method: Threaded stud single group Rating Method: Electrical single component all winding Thready Qty Per Inch (tpi): 20 single group
Mounting Method: Threaded stud single group Rating Method: Electrical single component all winding Thready Qty Per Inch (tpi): 20 single group Thread Size:
Mounting Method: Threaded stud single group Rating Method: Electrical single component all winding Thready Qty Per Inch (tpi): 20 single group Thread Size: 0.250 inches single group
Mounting Method: Threaded stud single group Rating Method: Electrical single component all winding Thready Qty Per Inch (tpi): 20 single group Thread Size: 0.250 inches single group Winding Operating Current:
Mounting Method: Threaded stud single group Rating Method: Electrical single component all winding Thready Qty Per Inch (tpi): 20 single group Thread Size: 0.250 inches single group Winding Operating Current: 400.0 milliamperes dc single component single winding
Mounting Method: Threaded stud single group Rating Method: Electrical single component all winding Thready Qty Per Inch (tpi): 20 single group Thread Size: 0.250 inches single group Winding Operating Current: 400.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms:
Mounting Method: Threaded stud single group Rating Method: Electrical single component all winding Thready Qty Per Inch (tpi): 20 single group Thread Size: 0.250 inches single group Winding Operating Current: 400.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 40.000 single component 2nd winding
Mounting Method: Threaded stud single group Rating Method: Electrical single component all winding Thready Qty Per Inch (tpi): 20 single group Thread Size: 0.250 inches single group Winding Operating Current: 400.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 40.000 single component 2nd winding Thread Series Designator:
Mounting Method: Threaded stud single group Rating Method: Electrical single component all winding Thready Qty Per Inch (tpi): 20 single group Thread Size: 0.250 inches single group Winding Operating Current: 400.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 40.000 single component 2nd winding Thread Series Designator: Unc single group
Mounting Method: Threaded stud single group Rating Method: Electrical single component all winding Thready Qty Per Inch (tpi): 20 single group Thread Size: 0.250 inches single group Winding Operating Current: 400.0 milliamperes dc single component single winding Dc Resistance Rating In Ohms: 40.000 single component 2nd winding Thread Series Designator: Unc single group Terminal Type And Quantity:

--

Unit Of Measure:

NSN 5950-00-235-6531

Reactor - Page 2 of 2



em			

No

Fiig:

A058b0