

View Online at <https://aerobasegroup.com/nsn/5950-00-235-6767>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.813 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.688 inches single mounting facility single center group

Impedance Rating In Ohms:

8000.0 single component single primary

Frequency Rating:

200.0 hertz single component and 5.0 kilohertz single component

Maximum Transformer Power Rating:

1.9 watts single component

Primary To Secondary Turn Ratio:

1 to 3-5/8 single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

2.547 inches

Body Width:

2.391 inches

Body Height:

3.031 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Winding Operating Current:

30.0 milliamperes dc single component single primary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

6 standoff, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0