

View Online at <https://aerobasegroup.com/nsn/5950-00-235-6773>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.812 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.812 inches single mounting facility single center group

Impedance Rating In Ohms:

8000.0 single component single primary

Frequency Rating:

7.0 kilohertz single component and 160.0 kilohertz single component

Maximum Transformer Power Rating:

3.0 watts single component

Primary To Secondary Turn Ratio:

1 to 17-7/10 to 20 single component

Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

Body Length:

2.250 inches

Body Width:

2.250 inches

Body Height:

3.188 inches

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thready Qty Per Inch (tpi):

32 single group

Thread Size:

0.138 inches single group

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0