

View Online at <https://aerobasegroup.com/nsn/5950-00-236-6391>

Reliability Indicator:

Not establishednot established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.875 inches single mounting facility single center group3.875 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.625 inches single mounting facility single center group2.625 inches single mounting facility single center group

Mounting Hole Diameter:

0.213 inches single group0.213 inches single group

Frequency Rating:

400.0 hertz single component400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single componentinternal shield brought out to terminal single component

Body Length:

4.656 inches 4.656 inches

Body Width:

3.218 inches 3.218 inches

Body Height:

4.120 inches 4.120 inches

Inclosure Type:

Fully enclosedfully enclosed

Mounting Facility Quantity:

4 single group4 single group

Mounting Method:

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 primary single component and 10 secondary single component10 secondary single component

Winding Operating Current:

85.0 milliamperes ac single component 2nd secondary

Winding Operating Voltage:

800.00 ac volts single component 2nd secondary

Special Features:

Primary winding; ten secondary windings

Terminal Type And Quantity:

26 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0