## NSN 5950-00-236-6772

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-236-6772

## **Reliability Indicator:**

Not establishednot established

## **Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.734 inches single mounting facility single center group and 1.734 inches single mounting facility single center group and 1.766 inches single mounting facility single center group and 1.766 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

1.344 inches single mounting facility single center group and 1.344 inches single mounting facility single center group and 1.406 inches single mounting facility single center group and 1.406 inches single mounting facility single center group

#### **Overall Height:**

3.000 inches 3.000 inches

#### **Overall Width:**

2.938 inches 2.938 inches

## **Mounting Slot Width:**

0.125 inches single group 0.125 inches single group

## **Frequency Rating:**

400.0 hertz single component400.0 hertz single component

## Input-output Phase Relationship:

Three phase to three phase single component and three phase to three phase single component and three phase to six phase single component componentthree phase to six phase single component

## **Transformer Winding Connection Type:**

Delta-delta and delta-delta and delta-wyedelta-wye

## **Body Length:**

2.250 inches 2.250 inches

## Inclosure Type:

Fully enclosedfully enclosed

## **Mounting Facility Quantity:**

4 single group4 single group

## **Mounting Method:**

Bracket single group and bracket single group and slot single groupslot single group

## Winding Function And Quantity:

1 primary single component and 1 primary single component and 2 secondary single component2 secondary single component

## **Winding Operating Current:**

31.0 milliamperes ac single component single primary

## Winding Power Rating:

19.5 volts-amperes single component single primary

## Winding Operating Voltage:

50.00 ac volts single component 2nd secondary115.00 ac volts single component 1st secondary

## **Terminal Type And Quantity:**

13 tab, solder lug

## Shelf Life:

N/a

#### **Unit Of Measure:**

--

## Demilitarization:

# NSN 5950-00-236-6772

Power Transformer - Page 2 of 2



Fiig:

A058b0