# NSN 5950-00-237-2107

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-00-237-2107

_								
D	$\sim$	lia	hi	litv,	Ind	lica	+~	
Г		на	IJΙ	IILV	IIIU	III	ιU	Ι.

Not establishednot established

### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group2.500 inches single mounting facility single center group

### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.125 inches single mounting facility single center group3.125 inches single mounting facility single center group

## **Mounting Hole Diameter:**

0.218 inches single group 0.218 inches single group

### Frequency Rating:

60.0 hertz single component60.0 hertz single component

### Input-output Phase Relationship:

Single phase to single phase single componentsingle phase to single phase single component

#### **Body Length:**

3.750 inches 3.750 inches

#### **Body Width:**

3.120 inches 3.120 inches

## **Body Height:**

3.500 inches 3.500 inches

### **Inclosure Type:**

Fully enclosedfully enclosed

# **Mounting Facility Quantity:**

4 single group4 single group

### **Mounting Method:**

Flange single group and flange single group and unthreaded hole single groupunthreaded hole single group

## **Winding Function And Quantity:**

1 primary single component and 1 primary single component and 6 secondary single component6 secondary single component

# **Winding Operating Voltage:**

81.48 ac volts single component 1st secondary and 86.52 ac volts single component 1st secondary

#### **Special Features:**

Iprimary: 6 secondary windings

## **Terminal Type And Quantity:**

18 tab, solder lug

## Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

Denninanzation

No

Fiig:

A058b0