

View Online at <https://aerobasegroup.com/nsn/5950-00-238-2709>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Frequency Rating:

400.0 hertz single component and 2.4 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.250 inches

Body Width:

2.875 inches

Body Height:

3.500 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group and unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 5 secondary single component

Special Features:

Primary winding 115 v rating, secondary windings rated 5.1 v at 2.0 amp, 6.4 v at 1.2 amp, 6.4 v at 9.4 amp w/center tap, 655.0 v at 210.0 ma w/center tap, and 880.0 v at 90.0 ma w/center tap and tapped at 12.6 v

Terminal Type And Quantity:

16 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0