NSN 5950-00-238-9441

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-00-238-9441

| Reliability Indicator: |
|--|
| Not established |
| Overall Length: |
| 11.000 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 7.500 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 8.000 inches single mounting facility single center group |
| Overall Height: |
| 8.375 inches |
| Frequency Rating: |
| 50.0 hertz single component and 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Winding Shielding Method: |
| Internal shield grounded to inclosure and core single component |
| Body Length: |
| 10.000 inches |
| Body Width: |
| 9.000 inches |
| Body Height: |
| 7.750 inches |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 6 single group |
| Mounting Method: |
| Threaded stud single group |
| Winding Function And Quantity: |
| 2 primary single component and 3 secondary single component |
| Thready Qty Per Inch (tpi): |
| 16 single group |
| Thread Size: |
| 0.375 inches single group |
| Winding Operating Current: |
| 500.0 milliamperes ac single component 1st secondary |
| Winding Operating Voltage: |
| 42.00 ac volts single component 3rd secondary42.00 ac volts single component 2nd secondary |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 10 solder stud |

NSN 5950-00-238-9441

Power Transformer - Page 2 of 2



| _ | | | | | |
|---|---|------------|---|----|----|
| • | n | 0 1 | • | 12 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0