

View Online at <https://aerobasegroup.com/nsn/5950-00-239-7535>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Salt spray resistant

Overall Length:

Between 3.990 inches and 4.010 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.990 inches single mounting facility single center group and 3.010 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.490 inches single mounting facility single center group and 1.510 inches single mounting facility single center group

Overall Height:

2.469 inches

Overall Width:

Between 1.990 inches and 2.010 inches

Inductance Rating:

0.20 millihenries single component single winding

Frequency Rating:

380.0 hertz 2nd component and 420.0 hertz 2nd component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Primary and secondary shielded and brought out to terminal all components

Maximum Operating Temp:

95.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

6 single group

Mounting Method:

Threaded hole single group

Rating Method:

Electrical single component single winding

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

940.0 milliamperes ac single component single secondary

Dc Resistance Rating In Ohms:

0.025 single component single winding

Winding Operating Voltage:

26.00 ac volts single component single secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

9 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0