## NSN 5950-00-240-0400

Power Transformer - Page 1 of 1



| view Online at https://aerobasegroup.com/nsn/5950-00-240-0400  |
|--|
| Mounting Slot Width:   |
| 0.687 inches single group  |
| Frequency Rating:  |
| 60.0 hertz single component  |
| Input-output Phase Relationship:   |
| Single phase to single phase single component  |
| Maximum Transformer Power Rating:  |
| 10.0 kilovolt-ampere single component  |
| Distance Between Mounting Facility Centers:  |
| 12.000 inches single mounting facility single center group   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Facility Quantity:  |
| 2 single group   |
| Mounting Method:   |
| Flange single group and slot single group  |
| Winding Function And Quantity:   |
| 1 primary single component and 1 secondary single component  |
| Winding Operating Voltage:   |
| 20.00 ac volts single component single secondary and 240.00 ac volts single component single secondary |
| Special Features:  |
| Taps brought to no-load tap changer operating handle under cover                                       |
| Terminal Type And Quantity:  |
| 3 standoff insulator and 2 standoff, solderless lug  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |
| No   |
| Fiig:  |
| A058b0   |